



DCN-FV Voting Panel



The unit allows attendance registration and six types of voting: parliamentary, audience response, multiple choice, opinion poll, rating and for/against.

The yellow LED confirmation indicators are used to prompt the user to indicate presence and to vote and to confirm registration of what is voted.

The unit has an external present contact, which can be used for an external present or fraud switch. Fingerprint readers are typical for the external present contact use. The blue LED unit active indicator shows that the system is in normal operation.

The unit can be click-to-fit mounted in a metal panel with a thickness of 2 mm or can be mounted in combination with DCN-FCOUP coupling pieces and DCN-FEC end caps in any surface.

The combination of the voting unit with the end caps is very stylish, and fits in both modern and traditionally designed meeting rooms.

The unit is connected to the Dual Delegate Interface (DCN-DDI).

- ▶ IF design award
- ▶ External Present contact
- ▶ LED vote confirmation indicators
- ▶ LED unit active indicator

Functions

Controls and Indicators

- Five voting buttons with yellow confirmation indicators to register: Present, yes (+), no (-) and abstain (x) (attendance registration, parliamentary voting and for/ against) Numerals: 1 to 5 (multiple choice or opinion polls, rating) Rating scale: - -, -, 0, +, ++ (audience response).
- One unit active indicator. The blue LED indicates that the system is in normal operation.
- One de-init/init button (rear side of the unit).

Interconnections

- 2 RJ11 connectors, one for connection to DCN-DDI Dual Delegate Interface and one for loop through.
- Connector for an external present contact (AMP173977-3 socket).

Technical Specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 82 mm
Weight	81 g
Color	Silver (RAL 9022)

Ordering Information

Model | Description

DCN-FV Voting Panel
flush mounted, silver

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by