



# DCN-FVU Flush Voting Unit



- ▶ **Stylish and modern design (IF award)**
- ▶ **Allows parliamentary voting, numerals and rating scale**
- ▶ **Easily mountable**
- ▶ **Direct loop through connection to the DCN network**
- ▶ **Economic solution for positions which only require voting facilities**

The Flush Voting Unit allows attendance registration and six types of voting: parliamentary, audience response, multiple choice, opinion poll, rating and for/against.

The yellow LED confirmation indicators prompt the user to indicate presence and to vote and to confirm registration of what is voted.

The blue LED unit active indicator shows that the system is in normal operation. The blue LED flashes when the unit detects a communication fault.

The combination of the voting unit with the end caps forms a very stylish design, which fits in both modern and traditional meeting rooms.

The direct connection to the DCN network cable results into an economic solution for positions which only require voting facilities

- Numerals 1 to 5 (used for multiple choice, opinion polls and rating)
- Rating scale: --, -, 0, +, ++ (used for audience response)

- One unit active indicator. A constant lit blue LED indicates that the system is in normal operation. The blue LED flashes when the unit detects a communication fault

Back

- One de-init/init button

#### Interconnections

- 1 m (39.4 in) DCN cable terminated with a molded six-pole male circular connector
- 1 m (39.4 in) DCN cable terminated with a molded six-pole female circular connector for loop-through connection to the DCN network

**Note** An unused output cable must be terminated with an LBB 4118/00 Termination Plug.

## Functions

### Controls and Indicators

Front

- Five voting buttons with yellow confirmation indicators to prompt the user to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:
  - Yes (+), no (-) and abstain (x) (used for attendance registration, parliamentary voting and for/against)

## Technical Specifications

### Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 82 mm (1.57 x 3.94 x 3.23 in)
Weight	250 g (0.55 lb)
Color	
DCN-FVU	Silver (RAL 9022)
DCN-FVU-D	Dark (graphite gray)

## Ordering Information

<b>DCN-FVU Flush Voting Unit</b> direct loop-through connection to DCN network, flush mounted, silver	<b>DCN-FVU</b>
--	----------------

<b>DCN-FVU-D Flush Voting Unit Dark</b> direct loop-through connection to DCN network, flush mounted, dark	<b>DCN-FVU-D</b>
---	------------------

### Accessories

<b>LBB 4118/00 DCN Termination Plug</b> use with opened-ended DCN cabling	<b>LBB4118/00</b>
--	-------------------

**Americas:**  
Bosch Security Systems, Inc.  
Communications Systems  
12000 Portland Avenue, South  
Burnsville, Minnesota 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
audiosupport@US.bosch.com  
www.boschcommunications.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3453  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by