



INT-TX Transmitters



The transmitter is the central element in the Integrus system. It accepts analogue or digital input, modulates these signals onto carrier waves and transmits these carrier waves to radiators located in the room.

Functions

- Auxiliary mode for distribution of music to all channels during a break
- Slave mode for distribution of signals from another transmitter allows multiple rooms to be used
- Test mode which produces a different frequency tone for each input/channel, with the tone gradually rising as the channels are stepped through
- Adjustable sensitivity for each input to enable fine tuning of audio levels
- Built-in mini infra-red radiator for audio monitoring
- Radiator and system status indication via display
- Each transmitter can be assigned a unique name by the installer for easy identification in a multi-transmitter system
- Each audio channel can also be assigned a unique name by the installer. These names can be selected from a list of options or entered manually
- Automatic distribution of emergency messages to all channels
- Automatic standby/on function
- Automatic synchronization to the number of channels in use in a DCN system
- Universal mains power facility allows use worldwide

- ▶ Can distribute a maximum of 4, 8, 16 or 32 audio channels
- ▶ Can be used with DCN Next Generation, or analogue systems like the CCS 800
- ▶ Flexible configuration of channels and channel quality modes for efficient distribution
- ▶ Configuration of transmitter and system via a display and one single rotary push button

- Stylish 19" (2U) housing for tabletop use or rack mounting
- Handgrips for easy transportation

Controls and Indicators

- 2 x 16 character LCD display for status information and transmitter configuration
- Rotary push button for navigation through menus and configuration
- Power on/off switch on front panel

Interconnections



Interconnections (at rear of transmitter)

- Male Euro socket for mains connection
- Slot with audio data bus connector (H 15, female) for accepting LBB 3422/20 Symmetrical Audio Input and Interpreters Module
- 4, 8, 16 or 32 cinch connectors for input of asymmetrical audio signals

- Two XLR sockets for input of symmetrical signals of floor, emergency messages or music
- One terminal block socket for distribution of emergency messages to all channels
- 3.5 mm (0.14 in) stereo headphone socket for monitoring inputs and channels
- One BNC connector for accepting an HF signal from another transmitter
- Six BNC connectors for output of HF signal to up to 30 radiators
- Two Optical Network Connectors for connection within a DCN Next Generation system*

* LBB 4416/xx Optical Network Cables required

Parts Included

Quantity	Component
1	INT-TX transmitter
1	19" rack mounting brackets, detachable feet and mounting accessories for modules included
1	System installation and operating manual on CD-ROM
1	Mains cable

Technical Specifications

Electrical

Mains voltage	90 to 260 V, 50 to 60 Hz
Power consumption operating, maximum	55 W
standby	29 W
Asymmetrical audio inputs	+3 dBV nominal, +6 dBV maximum (± 6 dB) +15 dBV nominal, +18 dBV maximum (± 6 dB)
Symmetrical audio inputs	+6 to +18 dBV nominal
Emergency switch connector	emergency control input
Headphone output	32 ohm to 2 kohm
HF input	nominal 1 Vpp, minimum 10 mVpp, 75 ohm
HF output	1 Vpp, 6 VDC, 75 ohm

Mechanical

Dimensions (H x W x D) for tabletop use, with feet	92 x 440 x 410 mm (3.6 x 17.3 x 16.1 in)
for 19" rack use, with brackets	88 x 483 x 410 mm (3.5 x 19 x 16.1 in)
in front of brackets	
behind brackets	40 mm (1.6 in) 370 mm (14.6 in)
Weight without brackets, with feet	6.8 kg (15.0 lb)
Mounting	brackets for 19" rack mounting or fixing to a tabletop Detachable feet for free-standing on a tabletop
Color	charcoal (PH 10736) with silver

Ordering Information

INT-TX04 4-Channel Transmitter

INT-TX08 8-Channel Transmitter

INT-TX16 16-Channel Transmitter

INT-TX32 32-Channel Transmitter

Accessories

INT-TXK04 Transmitter Upgrade Kit
4 channel

INT-TXK08 Transmitter Upgrade Kit
8 channel

INT-TXK16 Transmitter Upgrade Kit
16 channel

INT-TXK32 Transmitter Upgrade Kit
32 channel

LBB 3422/20 Symmetrical Audio Input and Interpreter Module

LBB 3423/20 DCN Interface Module

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by